

SSM-3

Silicone Spray Dispensing System

Reduce composite fabrication costs with spray-applied multi-use silicone vacuum bags.

<u>Spray-able</u> - Saves time, cuts costs and reduces handling

Workable - "net shape" conforms fully to tooling, even complex contours

Odorless - no odor, no solvents, no VOC's

Repairable - easily repairable with like material to extend the life of the bag



SWORL Reusable Vacuum Bags <u>www.SWORL.net</u>

Marine, Transportation, Wind, Industrial, Aerospace, Architectural



Sworl SSM-3 Spray Dispensing System

Several Features of this system are:

- 10:1 Fixed ratio fluid pumps
- (6 G.)/(23L.) Base Tank and (1.6 G.)/(5L.) Cat Tank
- Easy maneuverability on cart mounted model.
- No Maintenance gun. No internal seals. No moving parts.
- Momentary and continuous flow controls.
- Build rate:(Output)
- (1.52 Sq. Ft./min. @60 PSI) / (.141M2 /Min. @4.13 Bar)



Technical Specifications:

Weight: (42 lbs.)/(19 kg.)

Size: $(18" \times 15" \times 5") / (46 \text{cm} \times 38 \text{cm} \times 13 \text{cm}) * l$ Operating Pressure (35 - 60 psi)/(2.4 - 4.1 bar)Standard length hoses (9 ft)/(2.74m) *2

*1 Does not include tank height. *2 Optional hose lengths available.

SWORL, Inc. 602 E. Front Street Hutto, TX. 78634 Tel: (512)846-2444

Fax: (512)846-2400 Email: info@SWORL.net



Portable

SWORL Reusable Vacuum Bags www.SWORL.net

Marine, Transportation, Wind, Industrial, Aerospace, Architectural



Easy to use momentary or continuous spray gun controls.

Authorized Sworl Distributor